



CALFINN
QUALITY WORKSHOP EQUIPMENT

9/31 Governor Macquarie Drive, Chipping Norton, NSW
(M) 0419 101 317 (Office) 02 9548 5350 (Fax) 02 9520 1612



EG2460

Extra-short impact wrench



Half inch ex short 109mm


- Extra short body with huge torque output
- Reinforced, lightweight aluminium housing and alloy steel front bushing for durability
- Refined hammer impact mechanism
- 3 settings in forward, 3 in reverse
- One-hand operated
- Variable speed control with tease trigger
- Ergonomic comfort-grip handles

EG2460	
Capacity (square drive)	1/2"
Max free speed	9000 rpm
Max torque	677 Nm
Vibrations	4.5 m/s ²
Air inlet	1/4"
Air consumption	134 l/m
Max. air pressure	6.2 bar
Noise level	95 Dba
Weight	1.3 kg
Length	109 mm



EG2480

Extra-short impact wrench



- Extra short body with huge torque output
- Reinforced, lightweight aluminium housing and alloy steel front bushing, for durability
- Refined hammer impact mechanism
- 3 settings in forward, and 3 in reverse
- One-hand operated
- Variable speed control with tease trigger
- Ergonomic comfort-grip handle

EG2480	
Capacity (square drive)	3/8"
Max free speed	6500 rpm
Max torque	540 Nm
Vibrations	4.5 m/s ²
Air inlet	1/4"
Air consumption	134 l/m Max.
Max. air pressure	6.2 bar
Noise level	95 dBA
Weight	1.3 kg
Length	109 mm



EG2560 Composite impact wrench 1486 Nm



- Switch has 3 levels
- L/R changeable with just one 1 hand
- Short model for a better reach
- Powerful Twin hammer
- Low air consumption - 113 l/m
- Ergonomic comfort grip
- User can be right or left handed
- Ideal for every tire shop/fitter
- Low vibrations level

EG2560	
Capacity (square drive)	1/2"
Max free speed	8500 rpm
Max torque	1486 Nm
Vibrations	12.92 m/s ²
Air inlet	1/4"
Air consumption	113 l/m Max.
Max. air pressure	6.0 bar
Noise level	95 dBA
Weight	1.95
Length	171 mm



EG 553 Mini ratchet



EG 553	
Capacity (square drive)	1/4"
Max free speed	240 rpm
Max torque	32 Nm
Vibrations	10.5 m/s ²
Air inlet	1/4"
Air consumption	185 l/m Max.
Noise level	92 dBA
Weight	0.5
Length	120 mm

EG 552 Mini ratchet



EG 552	
Capacity (square drive)	3/8"
Max free speed	240 rpm
Max torque	32 Nm
Vibrations	10.5 m/s ²
Air inlet	1/4"
Air consumption	185 l/m Max.
Noise level	92 dBA
Weight	0.5 Kgs
Length	120 mm



EG01-3-C6-19R Orbital sander central vacuum, 2.5 mm orbit



- 2.5 mm \emptyset orbit
- Well-balanced
- 360° Air exhaust
- Low vibration
- Low Noise
- Central Vacuum
- Lightweight composite housing

EG01-3-C6-19R	
Pad diameter	150 mm
Max free speed	10,000 rpm
Vibrations	0.8 m/s ²
Air inlet	1/4"
Air consumption	310 l/m Max.
Sanding Stroke	2.5 mm
Max air Pressure	6.2 Bars
Noise level	80 DB- low noise
Weight	0.9 Kgs
Length	120 mm



EG01-C6-19R Orbital sander central vacuum, 2.5 mm orbit



- 5 mm \emptyset orbit
- Well-balanced
- 360° Air exhaust
- Low vibration
- Central Vacuum
- Lightweight composite housing

EG01-3-C6-19R	
Pad diameter	150 mm
Max free speed	10,000 rpm
Vibrations	0.8 m/s ²
Air inlet	1/4"
Air consumption	310 l/m Max.
Sanding Stroke	5 mm
Max air Pressure	6.2 Bars
Noise level	80 DB- low noise
Weight	0.9 Kgs
Length	120 mm



EG 1062 Mini pro polisher



- Polish pad 75 mm
- Air consumption 61 l/m
- Length 130 mm
- Low Noise

EG01-3-C6-19R	
Pad diameter	75 mm
No-load speed	6,000 rpm
Air inlet	1/4"
Air consumption	310 l/m Max.
Vibrations	0.8 m/s ²
Sanding Stroke	5 mm
Max air Pressure	6.2 Bars
Noise level	80 DB- low noise
Weight	0.9 Kgs

EG 910 Low profile impact socket set 12pc



30% Lower than traditional Sockets

- Low profile for use in restricted access areas
- Impact rated
- Cr-Mo phosphate black finish

Contents 10, 11, 12, 13, 14, 15, 17, 19, 20, 21 mm

EG 915 Low profile impact socket set 14pc



30% Lower than traditional Sockets

- Low profile for use in restricted access areas
- Impact rated
- Cr-Mo phosphate black finish

Contents 4, 6, 7, 8, 9, 10, 11, 12, 13, 15, 16, 17, 18, 19 mm