

Wheel Dollies



Ergonomical handle makes the wheel dolly easily controllable by just one mechanic.

Rollers with ball bearings for easy rotation and positioning of wheels onto hubs.

Capacity 250 kg

WD Mobile

Ideal for service trucks.
Easy and safe mounting, demounting and handling of heavy wheels for trucks and buses.



Spring loaded support for fast and easy storing.



The rollers have three positions each side for different wheels sizes.



Capable of handling wheels up to large 445/65 - 22.5".



WD-500

Capacity: 500kg

Sliding arms enables handling of wheels with diameter from Ø 260 mm-1380 mm.

foot operated lifting even with maximum load

ideal for lifting twin wheels on trucks and buses

Max Lifting Height: 730mm



Capacity 800 kg.

WD-800

Dual rollers fitted with bearings for separate rotation and positioning of wheels.



136 kg.



Position of cylinder provides clear access to operating area through the open frame.



Sliding arms. Enables handling of wheels with diameter from Ø 545 mm - 1278 mm.



Top-point wheel connection rod keeps the wheel in safe balance.

156 kg.

Capacity 1600 kg.

min. 190 mm max. 1080


Large Ø150 mm wheels for easy maneuverability.

Capable of handling large wheels from 1150 mm up to 2150 mm in diameter and up to 1050 mm in depth.
Easy to use outside the workshop.
Disassembled in a few seconds.

WD-1600



2 x 4 large rollers improve handling of tyres with deep treads.



hydraulic system, ands-free switch between lifting and lowering action. Safe and controlled lowering.

